

R304326 Connection Module Cat.5e, 1xRJ45/u, 100x

090.5327

**Warranty**

5 Years + extended warranty

Scope of supply

- RJ45 Cat.5e connection module, unshielded
- Mounting plate
- Dust cover
- Cable tie
- Installation instructions

Weight

8.000G

Approval

UL

Technical Data

Standardisation	IEC 60603-7: Electrical Characteristics of the Telecommunication Outlets ISO/IEC 11801, Second Edition: September 2002 EN 50173-1: May 2007
Connector type (A)	RJ45
Category connector (A)	Cat.5e
Shielding - connector (A)	No
Holder for connector / module	Support Plate
Wiring diagram	EIA/TIA 568A / EIA/TIA 568B
Poles	8
Material	plastic: PC, UL 94 V-0
Color	light gray
Dimensions	16.4 x 21.4 x 40.9 mm
Dispatch weight	8.000
Unit of dispatch weight	G

Tender text

Connection Module, Cat.5e, 100 x RJ45, unshielded

RJ45 connection module of Category 5, for the setting up of transmission channels of class D with up to 4 plugged connections, complies with Category 5 requirements of the standards ISO/IEC 11801:2002, EN 50173-1: May 2007, DIN-EN 50173-1: Dec. 2007 as well as ANSI/TIA/EIA 568-B.2-1, de-embedded tested in acc. with IEC 60603-7-2, interoperable and backwards compatible with Category 5e (2000) and Category 5 (1995).

Suitable for 1GBase-T applications in acc. with IEEE 802.3 over 100 m.

Tested in line with R&M's manufacturing control.

PCB-free and tool-free Easy-Lock connection of installation cables AWG 24 – 22 (0.5 mm – 0.65 mm) and flexible cables AWG 26/7 – AWG 22/7 (as of production date 07461). Parallel pair termination without crossover in acc. with EIA/TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with single-wire strain relief and >20 insertion cycles, contact resistance 1000 Veff, halogen-free materials, with integral cable strain relief.

Special installer package with connection module Cat.5e, with dust cover, mounting plate, cable tie and installation instructions.