

R305117 19" 1U Patch Panel 24xRJ45/u, Cat.6, fully populated

010.2065

**Warranty**

5 Years + extended warranty

Scope of supply

- 19" 1U 24-port metal patch panel, empty, integrated cable tie shelf
- 24 Cat.6 connection modules, RJ45/u incl. dust covers
- 19" mounting kit
- 4 labeling strips
- Cable ties
- Installation instructions

Weight

1281.000G

Approval

UL

Technical Data

Rack mounting version	Patch Panel
Connector type (A)	RJ45
Number of connectors (A)	24
Category connector (A)	Cat.6
Shielding - connector (A)	No
Holder for connector / module	Snap-In Frame
Assembly	fully populated
Material	steel: DC01 (1.0330), 1.5 mm
Color	blue, chromated
Dimensions	43.2 x 482.6 x 151.5 mm
Dispatch weight	1281.000
Unit of dispatch weight	G

Tender text

19" 1U Patch Panel, 24 x RJ45, Cat.6, unshielded

Patch panel with integrated cable tie shelf, 19" fastening kit, labeling field, accepting the snap-in type color coding clips in 8 colors.

Material: sub-rack made of sheet steel (DC01A) 1.5 mm, color blue chromated, screen made of plastic (ABS), halogen-free, color medium gray (NCS 2502-B)

Populated with 24 unshielded RJ45 connection modules of Category 6, for the establishing of transmission channels of class E with up to 4 plugged connections, complies with Category 6 requirements of the standards ISO/IEC 11801:2002, EN 50173-1: May 2007, DIN-EN 50173-1: Dec. 2007 as well as ANSI/TIA/EIA 568-B.2-1, de-embedded tested in acc. with IEC 60603-7-4, interoperable and backwards compatible with Cat.5e and Cat.5.

Suitable for 10GBase-T applications in acc. with IEEE 802.3an up to 500 MHz and 55 m.

Tested in line with R&M's manufacturing control, performing 100% inspection.

Compatible with RJ standard plugs (RJ11, RJ12, RJ45), PCB-free and tool-free Easy-Lock connection of installation cables AWG 24 – 22 (0.5 mm – 0.65 mm) and flexible cables AWG 26/7 – AWG 22/7. Parallel pair termination without crossover in acc. with EIA/TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with single-wire strain relief and >20 insertion cycles, contact resistance 1000 Veff. Halogen-free materials. With integral cable strain relief, including dust cover.

Mounting dimensions 14.9 x 19.5 mm, max. material thickness 1.6 mm.

Connection module Cat.6, unshielded, with dust cover, snap-in frame, cable tie and installation instructions.

Modules & Accessories

R302151	Snap-in Coding Clip, anthracite
R302152	Snap-in Coding Clip, blue
R302153	Snap-in Coding Clip, brown
R302154	Snap-in Coding Clip, green
R302155	Snap-in Coding Clip, red
R302156	Snap-in Coding Clip, violet
R302157	Snap-in Coding Clip, white
R302158	Snap-in Coding Clip, yellow
R305090	Labeling Sheet 24-Port Patch Panel
R306179	19" 1U Cable Management Plastic, 70 mm plastic ring
R306180	19" 2U Cable Management Plastic, 70 mm plastic ring
R306181	19" Lateral Radius Guard, left and right
R308708	Snap-in Blind Cover, light gray