

R35405 19" 3U Global Patch Panel 48xRJ45/u, Cat.5e, partly populated

090.5337

**Warranty**

5 Years + extended warranty

Description**Scope of supply**

- 19" 3U Global patch panel/u incl. cable tie shelf
- 12 connection module holders Global/u
- 3 Global blind covers
- 48 Cat.5e connection modules, RJ45/u incl. dust covers
- Labeling strips
- 19" mounting kit
- Cable ties
- Installation instructions

Weight

2400.000G

Technical Data

Rack mounting version	Patch Panel
Connector type (A)	RJ45
Number of connectors (A)	48
Category connector (A)	Cat.5e
Shielding - connector (A)	No
Holder for connector / module	Module Holder
Assembly	partly populated
Material	steel: DC01 (1.0330), 1.5 mm / aluminum / plastic: PA66, PC, fiber-glass reinforced, halogen-free
Color code NCS	S 2502-B
Color	medium gray
Dimensions	132.5 x 482.6 x 221 mm
Dispatch weight	2400.000
Unit of dispatch weight	G

Tender text

19" 3U Global Patch Panel, 48 x RJ45, Cat.5e, unshielded

Modular patch panel accommodating up to fifteen connection module holders Global /u, installation-friendly thanks to snap-and-go technique, Global blind cover or FiberModul 5.6HP. Designed to accommodate the R&M security and the R&M environment system, with its 3-level protection concept: color coding, mechanical coding, locking option.

Exchangeable labeling strips, integral cable tie shelf, fastening kit, labeling fields, tool-free locking and unlocking system.

Profile aluminum, colorless chromated; cable tie shelf sheet steel (DC01A) 1.5 mm, color blue passivated; side panel plastic (PA), fiberglass-reinforced, halogen-free, color medium gray (NCS 2502-B).

Including 12 connection module holders Global, unshielded, plastic (PC), halogen-free, color light gray (NCS 1005-R80B)

With 3 Global blind covers, plastic (PC), halogen-free, color light gray (NCS 1005-R80B)

Populated with 48 unshielded RJ45 connection modules of Category 5, for the setting up of transmission channels of class D with up to 4 plugged connections, complies with Category 5 requirements of the standards ISO/IEC 11801:2002, EN 50173-1: May 2007, DIN-EN 50173-1: Dec. 2007 as well as ANSI/TIA/EIA 568-B.2-1, de-embedded tested in acc. with IEC 60603-7-2, interoperable and backwards compatible with Category 5e (2000) and Category 5 (1995).

Suitable for 1GBase-T applications in acc. with IEEE 802.3 over 100 m.

Tested in line with R&M's manufacturing control.

PCB-free and tool-free Easy-Lock connection of installation cables AWG 24 – 22 (0.5 mm – 0.65 mm) and flexible cables AWG 26/7 – AWG 22/7 (as of production date 07461). Parallel pair termination without crossover in acc. with EIA/TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with single-wire strain relief and >20 insertion cycles, contact resistance 1000 Veff, halogen-free materials, with integral cable strain relief.

Connection module Cat.5e, unshielded, with dust cover, mounting plate, cable tie and installation instructions.

Modules & Accessories

R25107	Coding "A" for RJ45 Jack, anthracite
R25676	Coding "B" for RJ45 Jack, white
R304825	Plug Guard RJ45, green
R304826	Plug Guard RJ45, red
R304827	Plug Guard RJ45, white
R305685	Hinged Dust Cover, anthracite
R305686	Hinged Dust Cover, blue
R305687	Hinged Dust Cover, brown
R305688	Hinged Dust Cover, yellow
R305689	Hinged Dust Cover, gray
R305690	Hinged Dust Cover, green
R305691	Hinged Dust Cover, red
R305692	Hinged Dust Cover, violet
R305693	Hinged Dust Cover, white
R306058	Splash Cap IP54, blue
R306060	Splash Cap IP54, yellow
R306061	Splash Cap IP54, green
R306062	Splash Cap IP54, red
R306063	Splash Cap IP54, white
R306179	19" 1U Cable Management Plastic, 70 mm plastic ring
R306180	19" 2U Cable Management Plastic, 70 mm plastic ring
R306181	19" Lateral Radius Guard, left and right
R30871	Labeling Sheet Fiberliner / 3U Global Module Holder
R310835	Plug Reduction Frame RJ45 onto RJ11/RJ12
R316247	Global Cable Management 3-Ring, 70 mm plastic ring